

# P Series Spun-Bonded Polypropylene Cartridges



## Technical Specifications

Model	Maximum Dimensions (mm)	Micron Rating	Initial $\Delta$ P (psi) @ Flow Rate
P5-478	124 (H) x 60 ( Dia.)	5	<0.3 psi @ 2 gpm
P1	248 (H) x 60 ( Dia.)	1	<0.6 psi @ 5 gpm
P5	248 (H) x 60 ( Dia.)	5	<0.2 psi @ 5 gpm
P25	248 (H) x 60 ( Dia.)	25	<0.2 psi @ 5 gpm
P1-20	508 (H) x 60 ( Dia.)	1	<0.6 psi @ 10 gpm
P5-20	508 (H) x 60 ( Dia.)	5	<0.6 psi @ 10 gpm
P25-20	508 (H) x 60 ( Dia.)	25	<0.2 psi @ 10 gpm
P1-30	762 (H) x 60 ( Dia.)	1	<0.5 psi @ 10 gpm
P5-30	762 (H) x 60 ( Dia.)	5	<0.2 psi @ 10 gpm

## Benefits

- Manufactured from pure 100% polypropylene
- Designed for purity and chemical compatibility
- Spun fibers from a true gradient density from outer to inner surfaces
- The P1, P5, P1-20, and P5-20 is tested and Certified by NSF international to NSF/ANSI standard 42 for material requirements only