

WiLA™ Ultra Fine Filtration System



Model : **LS-307AE**

(Counter Top Type)

Dimension : 390H x 410L x 150W mm
(215H mm from outlet to table)

Electricity : N/A

Four Stage Filtration : **1st Stage - 5 micron, PP**
Sediment Reduction
2nd Stage - 5 micron, GAC Carbon Filter
Chlorine, Odor and THMs Reduction
3rd Stage - CTO Carbon Filter
Chemical, Chlorine, Odor and THMs Reduction
4th Stage - 0.01 Micron, Holow Fiber Membrane
Bacteria, Coliform Removal >99.9%

Flow Rate : 1 GPM

Max. Pressure : 80 psi

Max. Temperature : 45°C



Model : **LS-307C**

(Under Sink Type)

Faucet Model : DF-027

Dimension : LS-307C - 390H x 410L x 150W mm
DF-027 - 290H x 140W mm
(230H mm from outlet to table)

Electricity : N/A

Four Stage Filtration : **1st Stage - 5 micron, PP**
Sediment Reduction
2nd Stage - 5 micron, GAC Carbon Filter
Chlorine, Odor and THMs Reduction
3rd Stage - CTO Carbon Filter
Chemical, Chlorine, Odor and THMs Reduction
4th Stage - 0.01 Micron, Holow Fiber Membrane
Bacteria, Coliform Removal >99.9%

Flow Rate : 1 GPM

Max. Pressure : 80 psi

Max. Temperature : 45°C

No tools required



EASY TO OPERATE (easy change filter)

